

ZAP Controls

Forklift Radio Control Transmitters

4500-50

Description:

Forklift mounted transmitter. The transmitter features a heavy duty die-cast aluminum housing in a high visibility orange color and are rated for indoor use. The transmitter is designed to permanently mount to the forklift, eliminating the constant loss associated with handheld transmitters. The units permanently wire to the forklift battery system and offer a voltage range of 12 to 72 volts dc. Models are available in 1, 2, 4, and 6 channels.

ZAP part numbers:	4501-50	1 button
	4502-50	2 button
	4504-50	4 button
	4506-50	6 button

Case dimensions:

Length:	4-1/2"
w/ antenna:	6-3/4"
Width:	2-1/2"
Depth:	2-3/16"

Works with: 840 Receiver

Battery: None

Frequency: 433.92 Mhz.

Operating temperature:

-13 deg F to + 149 deg F



4500-66

Description:

Forklift mounted transmitter. The transmitter features a heavy duty die-cast aluminum housing in a high visibility orange color and are rated for outdoor use. The transmitter is designed to permanently mount to the forklift, eliminating the constant loss associated with handheld transmitters. The units permanently wire to the forklift battery system and offer a voltage range of 12 to 72 volts dc. Models are available in 1, 2, 4, and 6 channels.

ZAP part numbers:	4501-66	1 button
	4502-66	2 button
	4504-66	4 button
	4506-66	6 button

Case Dimensions:

Length:	4-1/2"
w/ antenna:	6-3/4"
Width:	2-1/2"
Depth:	2-3/16"

Works with: 840 Receiver

Battery: None

Frequency: 433.92 Mhz.

Operating temperature:

-13 deg F to + 149 deg F



ZAP Series 3 Simply Logical

ZAP Controls
100 Waterloo Blvd. Anglesey Business Park, Littleworth Road, Cannock, Staffordshire, England
UK Office Number 011-44-154-387-9444 sales@zap-uk.com
USA Contact 931-510-4432 sales@zap-america.com
USA Tech Support 931-510-4432 via telephone or text
Online www.zap-uk.com